

ENVIROREND

Compilation date: 29/01/2016 Revision No: 1 Authorised by: M.Gee

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: ENVIROREND BASECOAT

Product code: ESPS/EXG-BC Product Safety Data: EOI04.29

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: SPS Envirowall Ltd

Orchard House,

Aire Valley Business Centre

Keighley

West Yorkshire BD21 3DU **Tel:** 01535661633

Fax: 01535661933

Email: info@spsenvirowall.co.uk

1.4. Emergency telephone number

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: STOT SE 3: H335; Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1A: H317 Most important adverse effects: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye

damage. May cause respiratory irritation.

2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.H335: May cause respiratory irritation.

Hazard pictograms: GHS05: Corrosion

GHS07: Exclamation mark





Signal words: Danger

Precautionary statements: P280: Wear protective gloves/protective clothing/eye protection/face protection.



ENVIROREND

P302+352: IF ON SKIN: Wash with plenty of water/.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER/doctor/.

P321: Specific treatment (see instructions on this label).

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

WHITE CEMENT

266-043-4	65997-15-1	-	Skin Irrit. 2: H315; Skin Sens. 1A: H317; Eye Dam. 1: H318; STOT SE 3:	10-30%
PORTLAND (CEMENT		H335	
266-043-4	65997-15-1	-	Skin Irrit. 2: H315; Skin Sens. 1A: H317; Eye Dam. 1: H318; STOT SE 3: H335	1-10%
HYDRATED L	_IME - REACH re	gistered number(s): 01-2	119475151-45-0135	
215-137-3	1305-62-0	-	STOT SE 3: H335; Skin Irrit. 2: H315; Eye Dam. 1: H318	1-10%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist

examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe

pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.



ENVIROREND

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised

personnel. Do not attempt to take action without suitable protective clothing - see section

8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.

SPSELtd/Sales/2507 Page 3 of 7 VERSION 3 – MAY16



ENVIROREND

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

WHITE CEMENT

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL	
EU	-	-	4mg/m³	-	
POPTI AND CEMENT					

FORTLAND CEIVIENT

EU - 4mg/m³

HYDRATED LIME

EU	1mg/m³	4mg/m³	-	-

DNEL/PNEC Values

Hazardous ingredients:

HYDRATED LIME

Type	Exposure	Value	Population	Effect
PNEC	Fresh water	490µg/L	-	-
PNEC	Soil (agricultural)	1080mg/L	-	-

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

SPSELtd/Sales/2507 Page 4 of 7 VERSION 3 – MAY16



ENVIROREND

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HYDRATED LIME

DERMAL	RBT	LD50	>2500	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe

pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity



ENVIROREND

Hazardous ingredients:

HYDRATED LIME

FRESHWATER ALGAE	48H EC50	184.57	mg/l
FRESHWATER ALGAE	72H NOEC	48	mg/l
Freshwater fish	96H LC50	50.6	mg/l
Freshwater invertebrates	48H EC50	49.1	mg/l
Marine water fish	96H LC50	457	mg/l
Marine water invertebrates	14d NOEC	32	mg/l
Marinewater invertebrates	96H LC50	158	mg/l
Soil macroorganisms	EC10/LC10	2000	mg/kg
Soil microorganisms	EC10/LC10	12000	mg/kg
Terrestrial plants	21d NOEC	1080	mg/kg

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.



ENVIROREND

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage. H335: May cause respiratory irritation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.