



		SPS Envirowall Lt	d		
Spsicnvirowall Safety Data Sheet according to (EC) 1907/2006 - Artclie 31					
ISO No.		Version 2	Date prepar	ed: May 2022	
CTION 1 Identification of the a 1.1 Product identifier	article and of the compa	ny/undertaking			
Trade Name: Identification of the	Cement'in Mega Plus Light Product Name: Cement'in Product Code: ESPS/MPL-	Mega			
1.2 Relevant identified uses of th		ticle and uses advised a	gainst		
1.3 Details of the supplier of the Supplier	safety data sheet SPS Envirowall Ltd Lonsdale Chambers Lonsdale Street Stoke on Trent Staffordshire ST4 4BT Email: info@spsenvirowall. Telephone: 08451300983	.co.uk			
1.4 Emergency telephone No.	NHS : 111				
CTION 2 Hazards identificatio					
Regulation CLP (CE) n°.	 H315 Causes skin irritation H317 May cause an allergic H318 Causes serious eye d H335 May cause respirator 	skin reaction - Categor amage - Category (Eye	Dam.1)		
2.2 Label elements					
Label In compliance with EC Hazard pictograms:	regulation No 1272/2008 (GHS05 Corrosive material GHS07 Toxicity irritant cat	cat. 1	>		
	Danger Cement and/or chalk H 315 Causes skin irritation H 317 May cause an allergi H 318 Causes serious eye o H 335 May cause respirato	c skin reaction. Jamage.			
Precautionary statements:	 P 101 If medical advice is n P 102 Keep out of reach of P 280 Wear protective glo P 305+P351+P338 IF IN EY possible. Continue rinsing. P 310 Immediately call a Pr P 333+P313 If skin irritation 	^E children. oves/protective clothing, ′ES: rinse cautiously with OISON CENTER or docto	/eye protection/face prote water for several minutes or.	ction. Remove contact lenses, if present and	
2.3 Other hazards Information for environment: PBT assessment: vPvB assessment:	Not applicable				
CTION 3 Composition/inform	ation on ingredients				
3.1 Substances: 3.2 Mixtures/substances:	 The preparation is based of Cements Quartz sand and aggrega Possibly additives 			dous additives.	
Components presenting a (h Substance Name		EINECC	Concentration	Classification (DECULATION (EC)	
Substance Name	CAS No	EINECS:	Concentration	Classification (REGULATION (EC) No 1272/2008)	
Cement according to EN 197-1	65997-15-1	266-043-4	10-45%	H 315 Causes skin irritation. H 317 May cause an allergic skin reaction. H 318 Causes serious eye damage. H 335 May cause respiratory irritation.	
Chalk according to EN 459-1	CAS: 1305-62-0 (HL) CAS: 85117-09-5 (NHL)	215-137-3 285-561-1	O-35%	H 315 Causes skin irritation. H 317 May cause an allergic skin reaction. H 318 Causes serious eye damage. H 335 May cause respiratory irritation.	

Quartz sands/aggregates according to EN 13139 and/or EN 12620 (*) Limestone filler (*) 471-34-1 207-439-9 0-15%

(*) Substance for which there are exposure limits, according to community exposure limits, for workplace (consult section 8)

14808-60-7

238-878-4

40-80%

Not applicable

Not applicable





SECTION 4 Einst aid management			
SECTION 4 First aid measures 4.1 Description of first aid mea			
General Remark	 sures s: Remove person from the danger area and get medical attention. Bring with you this material data sheet. n: Rinse nose & throat with clean water (only if the person is conscious). Remove person to fresh air and keep comfortable for breathing. Get medical attention if symptoms are severe or persist. 		
Eye contac	: Do not rub in order to avoid further damage to the cornea. Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rins for at least 15 minutes and get medical attention. Bring with you this material safety data sheet.		
Skin contac	 t: Beware of the product that may remain between skin & clothing, watch, shoes, etc In case of allergic reaction, get medical attention. When the contaminated area is extensive and / or if there are skin injuries, it is necessary to get medical attentior or transfer to a hospital. If the powder is dry, remove the dust as much as possible and wash with plenty of water. If powder is mixed with water, wash with plenty of water. 		
Ingestion	n: If the quantity is low, rinse the mouth with water and get medical attention. In case of a larger quantity, do not give a drink; do not induce vomiting, transfer the person to a hospital and show the bag with label and/or material data sheet of the product.		
4.2 Most important symptoms a	and effects, both acute and delayed		
	 S: Any eye contact with cement (dry or wet) may cause serious eye damage potentially irreversible Cement may have an irritating effect on wet skin (through perspiration or ambient humidity) after prolonged contact, or may cause allergic reaction (eczematous dermatitis) after repeated contact. A prolonged skin contact with wet cement or wet mortar/concrete may cause severe burns because they occur without the person experiencing pain (this can occur e.g. by kneeling in the concrete, even through the pants). 		
	n: Repeated inhalation of cement dust over a long period increases the risk of developing lung diseases. e medical attention and special treatment needed No important information is available.		
SECTION 5 Fire-fighting measu			
5.1 Extinguishing media	In case of fire, use fire-extinguishing agent suitable in the form of powder (foam or CO2) for the surrounding fire or any other authorized agent. The product is not flammable.		
5.2 Special hazards arising from	n the substance or mixture There is no risk of fire or explosion. No important information is available.		
Protective actions durin	n Wear a suitable breathing apparatus to enter rooms full of smoke. g No specific firefighting precautions are necessary.		
firefighting SECTION 6 Accidental release			
	inclusion of the second s		
	S: Avoid contact with skin and eyes. Avoid breathe in the dust. Wear a suitable dust mask in case of sincere dust formation. Provide proper ventilation.		
6.1.2 For rescuer	s: Avoid contact with skin and eyes. Avoid breathe in the dust. Wear a suitable dust mask in case of sincere dust formation. Provide proper ventilation. Rescuers will be equipped with appropriate personal protection (refer to section 8).		
6.2 Environmental precautions	Place waste containers for residual waste according to the local regulation. If the product contaminates waterways, rivers or sewers, alert the relevant authorities according to the prescribed procedures. Avoid pouring large quantities of powder into sewers and surface water.		
6.3 Methods and material for co	Use mechanical clean up methods that do not cause airborne dispersion and deposit it into an appropriate container.		
6.4 Reference to other sections	Consult section 8 for information about personal protection equipment.		
CECTION 7 Handling and store	Consult section 13 for information about waste disposal.		
SECTION 7 Handling and stora 7.1 Precautions for safe handlir			
	n: There is not specific measure.		
Recommended equipment	 A Avoid imperatively skin and eye contact with the product. S: Wash hands after each use. Remove and wash contaminated clothing before re-use. Handle preferably in sufficiently ventilated rooms or outdoor. Avoid dust formation during use. If it cannot be avoided, wear a dust mask 		
	& It is forbidden to smoke, eat and drink in the rooms where the mixture is used.		
procedure	S:		
procedure 7.2 Conditions for safe st	S:		
procedure 7.2 Conditions for safe st Storage Packaging	s: torage, including any e: Keep away from water or humidity. Keep only original closed packaging into a dry place. Avoid dust dispersion.		

TECHNICAL INFORMATION



SECTION 8 Exposure controls/personal protection

Additional indications for the layout of technical installations

8.1 Control parameters

The product does not contain significant quantities of substances for the threshold values to be monitored on the workspace.

Components with limit values to be monitored at the workplace.

CAS No	Designation of the substance	Exposure limit values
CAS: 65997-15-1 EINECS: 266-043-4	Cement according to EN 197-1	MAC (NL) 10 mg/m ³ VLEP/GW(B) 10 mg/m ³ VME(FR) 10 mg/m ³ - total dust VME(FR) 5 mg/m ³ - alveolar dust DNEL(FR)-professional inhalation [mg/m ³] : (alveolar) 3 TWA(UK) 10 mg/m ³
CAS: 1305-62-0 (HL) EINECS: 215-137-3 CAS: 85117-09-5 (NHL) EINECS: 285-561-1	Chalk according to EN 459-1	MAC (NL) 5 mg/m ³ GW(B) 5 mg/m ³ VME(FR) 5 mg/m ³ TWA(UK) 5 mg/m ³
CAS: 14808-60-7 EINECS: 238-878-4	Quartz sands/aggregates according to EN 13139 and/or EN 12620	MAC (NL) 0,075 mg/m ³ GW(B) 0,075 mg/m ³ VME(FR) 0,075 mg/m ³ TWA(UK) 0,075 mg/m ³ These limits apply only to respirable dust.
CAS: 471-34-1 EINECS: 207-439-9	Limestone filler	MAC (NL) 10 mg/m ³ GW(B) 10 mg/m ³ VME(FR) 10 mg/m ³ TWA(UK) 10 mg/m ³

			VME(FR) 10 mg/m ³ TWA(UK) 10 mg/m ³	
8.2 Exposure controls General safety & hygiene measures:	The usual precautions for the chemical handling must be followed. Remove contaminated clothing immediately. Wash hands before breaks & after handling the product. Avoid eye contact. If necessary, use a moisturizing cream after using the product.			
Technical measures:	: Ensure that ventilation is appropriate or that there is an exhaust system at the workplace			
Individual protective equipment measures:	e Safety Pictogram 🏾 👔 🦳 🎧			
Eyes/face protection:	Before any handling of powders or dust emission, it is necessary to wear safety glasses or a hermetic protective mask according to EN 166.			
Hands protection:	: Wear suitable protection gloves, alkali-resistant and chemical agents resistant according to EN 374. The selection of gloves should be made according to the application & the duration of use at the workplace.			
	 Avoid skin contact. After contact with the product, all contaminated body parts should be washed. Wear suitable protection clothing. 			
Respiratory protection:	: In case of good ventilation, a respiratory protection is not necessary. In case of brief or low exposure to dust, use a P2 respiratory protection mask. Wearing a respiratory protection device is recommended in case of prolonged or repetitive exposure. The type of respiratory protection must be adapted to the level of dust concentration encountered and in accordance with applicable European norms (e.g. EN 149) or national standards.			
SECTION 9 Physical and chemica	al properties			
Appearance:	Powder			
	Varies according to the pr	roduct description.		
Odour:	Undetermined.	oduct description.		
Odour: Odour threshold value:	Undetermined. Undetermined.	oduct description.		
Odour: Odour threshold value: pH value:	Undetermined. Undetermined. PH>12	oduct description.		
Odour: Odour threshold value: pH value: Melting Point:	Undetermined. Undetermined. PH>12 Not applicable.	oduct description.		
Odour: Odour threshold value: pH value: Melting Point: Boiling Point:	Undetermined. Undetermined. PH>12 Not applicable. Not applicable.	oduct description.		
Odour: Odour threshold value: pH value: Melting Point: Boiling Point: Flash point:	Undetermined. Undetermined. PH>12 Not applicable. Not applicable. Not applicable.			
Odour: Odour threshold value: pH value: Melting Point: Boiling Point: Flash point: Inflammability (solid, gas):	Undetermined. Undetermined. PH>12 Not applicable. Not applicable. Not applicable. The product is not flamma			
Odour: Odour threshold value: pH value: Melting Point: Boiling Point: Flash point:	Undetermined. Undetermined. PH>12 Not applicable. Not applicable. Not applicable. The product is not flamma Not applicable.			
Odour: Odour threshold value: pH value: Melting Point: Boiling Point: Flash point: Flash point: Inflammability (solid, gas): Disaggregation temperature:	Undetermined. Undetermined. PH>12 Not applicable. Not applicable. Not applicable. The product is not flamma Not applicable.	able.		
Odour: Odour threshold value: pH value: Melting Point: Boiling Point: Flash point: Inflammability (solid, gas): Disaggregation temperature: Self-ignition: Explsion hazard:	Undetermined. Undetermined. PH>12 Not applicable. Not applicable. Not applicable. The product is not flamma Not applicable. The product is not self-igr The product does not pre	able. nitable.		
Odour: Odour threshold value: pH value: Melting Point: Boiling Point: Flash point: Inflammability (solid, gas): Disaggregation temperature: Self-ignition: Explsion hazard: Explosive limits:	Undetermined. Undetermined. PH>12 Not applicable. Not applicable. Not applicable. The product is not flamma Not applicable. The product is not self-igr The product does not pre Not applicable.	able. nitable.		
Odour: Odour threshold value: pH value: Melting Point: Boiling Point: Flash point: Inflammability (solid, gas): Disaggregation temperature: Self-ignition: Explsion hazard:	Undetermined. Undetermined. PH>12 Not applicable. Not applicable. Not applicable. The product is not flamma Not applicable. The product is not self-igr The product does not pre Not applicable.	able. nitable.		
Odour: Odour threshold value: pH value: Melting Point: Boiling Point: Flash point: Inflammability (solid, gas): Disaggregation temperature: Self-ignition: Explosive limits: Vapour pressure by 20°C:	Undetermined. Undetermined. PH>12 Not applicable. Not applicable. Not applicable. The product is not flamma Not applicable. The product is not self-igr The product does not pre Not applicable.	able. nitable.		
Odour: Odour threshold value: pH value: Melting Point: Boiling Point: Flash point: Inflammability (solid, gas): Disaggregation temperature: Self-ignition: Explosive limits: Vapour pressure by 20°C: Bulk Density: Relative Density:	Undetermined. Undetermined. PH>12 Not applicable. Not applicable. Not applicable. The product is not flamma Not applicable. The product is not self-igr The product does not pre Not applicable. Not applicable. 1.4 - 2 gr/cm ³ Not determined.	able. nitable.		
Odour: Odour threshold value: pH value: Melting Point: Boiling Point: Flash point: Inflammability (solid, gas): Disaggregation temperature: Self-ignition: Explosive limits: Vapour pressure by 20°C: Bulk Density: Relative Density: Vapour Density:	Undetermined. Undetermined. PH>12 Not applicable. Not applicable. The product is not flamma Not applicable. The product does not pre Not applicable. Not applicable. $1.4 - 2 \text{ gr/cm}^3$ Not determined. Not applicable.	able. nitable.		
Odour: Odour threshold value: pH value: Melting Point: Boiling Point: Flash point: Inflammability (solid, gas): Disaggregation temperature: Self-ignition: Explosive limits: Vapour pressure by 20°C: Bulk Density: Relative Density: Vapour Density: Evaporation rate:	Undetermined. Undetermined. PH>12 Not applicable. Not applicable. The product is not flamma Not applicable. The product is not self-ign The product does not pre Not applicable. Not applicable. 1.4 - 2 gr/cm ³ Not determined. Not applicable. Not applicable. Not applicable. Not applicable.	able. nitable.		
Odour: Odour threshold value: pH value: Melting Point: Boiling Point: Flash point: Inflammability (solid, gas): Disaggregation temperature: Self-ignition: Explosion hazard: Explosive limits: Vapour pressure by 20°C: Bulk Density: Relative Density: Vapour Density: Evaporation rate: Solubility in / mix-ability with water:	Undetermined. Undetermined. PH>12 Not applicable. Not applicable. Not applicable. The product is not flamma Not applicable. The product is not self-ign The product does not pre Not applicable. Not applicable. 1.4 - 2 gr/cm ³ Not determined. Not applicable. Not applicable. Not applicable. Not applicable. Not applicable. Insoluble in water.	able. nitable.		
Odour: Odour threshold value: pH value: Melting Point: Boiling Point: Flash point: Inflammability (solid, gas): Disaggregation temperature: Self-ignition: Explsion hazard: Explosive limits: Vapour pressure by 20°C: Bulk Density: Vapour pressure by 20°C: Bulk Density: Vapour Density: Vapour Density: Evaporation rate: Solubility in / mix-ability with water: Partition coefficient (n- octanol/water):	Undetermined. Undetermined. PH>12 Not applicable. Not applicable. The product is not flamma Not applicable. The product does not pre Not applicable. Not applicable. $1.4 - 2 \text{ gr/cm}^3$ Not determined. Not applicable. Insoluble in water. Not applicable.	able. nitable. sent an explosion risk.		
Odour: Odour threshold value: pH value: Melting Point: Boiling Point: Flash point: Inflammability (solid, gas): Disaggregation temperature: Self-ignition: Explsion hazard: Explosive limits: Vapour pressure by 20°C: Bulk Density: Vapour pressure by 20°C: Bulk Density: Vapour Density: Vapour Density: Evaporation rate: Solubility in / mix-ability with water: Partition coefficient (n- octanol/water):	Undetermined. Undetermined. PH>12 Not applicable. Not applicable. The product is not flamma Not applicable. The product is not self-ign The product does not pre Not applicable. 1.4 - 2 gr/cm ³ Not determined. Not applicable. Not applicable. Insoluble in water. Not applicable. Dynamic to 20 °C: Not ap Kinematic: Not applicable Oxidising properties: Not	able. nitable. sent an explosion risk. plicable.		





	group of comparing
SECTION 10 Stability and reactive	rity.
10.1 Reactivity	There are no dangerous reactions under normal conditions of use.
10.2 Chemical stability	There are no dangerous reactions under normal conditions of use.
10.3 Thermic decomposition	There are no dangerous reactions under normal conditions of use.
/conditions to avoid	
10.4 Possibility of hazardous	Reactions with acids. Reactions with common metals in presence of moisture (water) to form hydrogen.
reactions	
10.5 Conditions to avoid	Minimise exposure to air and moisture to avoid loss of product quality.
10.6 Incompatible materials	After contact with water, the product hardens.
10.7 Hazardous decomposition	There is no dangerous decomposition product known.
products	
SECTION 11 Toxicological inform	nation
11.1 Information on toxicological	
11.1.1 Substances	
	Deine mit imit ent off out
Acute toxicity:	Primary irritant effect
	Cement CAS 65997-15-1 by dermal route: LD50 = 2000 mg/KG Species: Rabbit
Skin Contact:	Skin irritation possible.
	The product may cause an irritation of the respiratory tract.
-	Strong irritant effect with risk of serious eye damage.
Ingestion:	Ingestion may cause severe irritation if the mouth, esophagus, gastrointestinal tract and vomiting.
Delayed Effects	
=	Not sensitizing.
	This mixture has not been tested. Consult section 11.1.
SECTION 12 Ecological informat	
12.1 Toxicity	Aquatic toxicity: however, adding large quantities of cement to the water can cause a rise in pH, and can therefore be toxic to aquatic life under certain conditions.
12.2 Persistence and degradability	There is no major information available. The hard product is permanently fixed and insoluble.
12.3 Bioaccumulative potential	There is no major information available.
	There is no major information available.
12.4 Mobility in soil	
12.5 Results of PBT & vPvB	PBT: Not applicable. vPvB: Not applicable
assessment	
12.6 Other adverse effects	There is no major information available.
SECTION 13 Disposal considerat	
Waste treatment methods	After setting, the product can be disposed as other construction residues.
	Dispose of uncleaned packaging according to local applicable regulations or government regulations. Empty the packaging completely.
Unused waste residue / prod	Dispose of uncleaned packaging according to local applicable regulations or government regulations. Do not pour
onused waste residue / prou	into drains or waterways.
CECTION 14 Transmost informati	
SECTION 14 Transport informati	
14.1 UN number	Not relevant
(ADR, ADN, IMDG, IATA)	
14.2 UN proper shipping name	Not relevant
(ADR, ADN, IMDG, IATA)	
14.3 Transport hazard class(es)	Not relevant
(ADR, ADN, IMDG, IATA)	
14.4 Packaging group	Not relevant
(ADR, ADN, IMDG, IATA)	
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
	to Annex II of MARPOL 73/78 and the IBC code
	Not applicable. Non dangerous according to the regulation mentioned above.
SECTION 15 Regulatory information	
**	ental regulations/legislation specific for the substance or mixture
Specific Dispositions:	France: Sheet of professional diseases (n°8: diseases due to cement). Ensure that national or local regulations are
	respected.
Others:	No data available.
15.2 Chemical safety assessment	

15.2 Chemical safety assessment No data available.

SECTION 16 Other information

As the users working conditions are not known to us, the information given in this material safety data sheet is based on the state of our knowledge and on both National and Community regulations. The product must not be used for other purposes than those specified in section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary measures to meet the requirements of local laws and regulations. The information mentioned in this sheet should be considered as a description of the safety requirements for our product and not as a guarantee of property of it.

DISCLAIMER OF LIABILITY

DISCLAIMENCY CLAMENCY CLAMENCY

SPS Envirowall Ltd nor any other subsidiary of the Benx Group will be held accountable for any damage resulting from handling or from contact with the above product. This data sheet and the information it contains is not intended to supersede any terms or conditions of sale and does not constitute a specification. Nothing contained herein is to be construed as a recommendation for use in violation of any patent or applicable laws or regulations.



