

Declaration of Performance

| | |
|---|--|
| DoP No: | RCM0007 |
| Product Description | Gypsum board made of a treated, water-resistant core, surfaced with fiberglass mats. |
| Brand name and/or product code | Densglass |
| Intended use in accordance with hEN as foreseen by manufacturer: | Rainscreen, masonry facades, fibre Cement sidings, timber Cladding and external Wall Insulation Systems. |
| Registered trade name of manufacturer and contact address: | Benx Ltd, Lonsdale Chambers, Lonsdale Street, Stoke on Trent, ST4 4BT |
| System of assessment and verification of consistency of performance of named product(s): | AVCP System 1 (reaction to Fire) AVCP System 3 (Other) |
| Harmonised Standard: | Warrington - Certification (I121) Performed Initial and continuous surveillance of the place of manufacture and the factory production control implemented sampled product and witnessed initial type testing under system 1 and issued: The Certificate of Constancy of Performance and the Certificate of Conformity of the Factory Production Control. |

| Declared performance | | |
|--|-------------|------------------------------------|
| Essential characteristic | Performance | Harmonised technical specification |
| Reaction to fire | A1 | EN 13501-1:2007 |
| Flexural Strength | ≥ 356 | EN 15283-1:2008/A1:2009 |
| Shear Strength | NPD | |
| Direct air borne sound insulation | NPD | |
| Acoustic absorption | NPD | |
| Impact Resistance | NPD | |
| Water vapour transmission g/ m ² /day | >970 | BS EN ISO 12572 |
| Thermal conductivity | 0.21 W/mK | BS EN12524 |

The performance of RCM Y-Wall is in conformity with the declared performance.

This declaration of performance is issued under the sole responsibility of Roofing & Cladding Materials Ltd.

Signed for and on behalf of Roofing & Cladding Materials Ltd.

Dr K. Ruane

Dr Kevin Ruane - Group Chief Executive Officer